

TRL PLUS



Supporti Rotore in fusione monoblocco
Rotor supports in monobloc casting
Giessen Teile
Supports rotor en coulée monobloc
Piezas únicas de fundición




2XCUT


Mazza doppio tagliente
Double cutting hammer
Hammerschlegel mit doppelt Schnitt
Marteau à double tranchant
Martillo de doble corte



- A Ø 614 mm
- B Ø 194 mm
- C Ø 194 mm
- V 60 m/sec



- Dotazioni di serie**
- Attacco al trattore Cat. 2
 - Trasmissione a bagno d'olio con ruota libera
 - Cinghie dentate
 - Cuscinetti rotore a doppio rullo oscillante
 - Rotore Bilanciato elettronicamente
 - Rullo di appoggio con raschia rullo regolabile in altezza
 - Portellone posteriore amovibile per manutenzione



	A	B
	cm	cm
TRL PLUS 230	127	154
TRL PLUS 250	127	167
TRL PLUS 280	163	165
TRL PLUS 300	178	175

- Standard equipment**

 - Tractor linkage Cat. 2
 - Oil sealed transmission with free wheel
 - Toothed belts
 - Rotor bearings with double oscillating roller
 - Electronically balanced rotor
 - Supporting roller with adjustable in height scraper
 - Rear removable hatch for maintenance
- Standardausstattung**

 - Traktor Anhängung Kat.2
 - Ölbad-Getriebe mit Freilauf
 - Gezackte Treibriemen
 - Rotor Lager mit doppel-schwankendem Roller
 - Rotor elektronisch balanciert
 - Verstellbare Stützwalze selbstreinigend mit Erdkratzer
 - Heckklappe für Wartung abnehmbar
- Equipamiento estándar**

 - Attelage tracteur Cat.2
 - Transmission bain d'huile avec roue libre
 - Courroies dentées
 - Roulements rotor à double rouleau oscillant
 - Rotor équilibré électroniquement
 - Rouleau d'appui avec décrottoir réglable en hauteur
 - Capot arrière amovible pour entretien
- Équipement de série**

 - Conexión Cat. 2
 - Transmisión con rueda libre
 - Correas dentadas
 - Rodamientos rodillos oscilantes doble (rotor)
 - Rotor balanceado electronicamente
 - Rodillo de apoyo con raspador ajustable
 - Portalón trasero para manutención amovible

	 A - B - C (mm)	 mm - inch	 G/min	 CV - KW	 N °	 Kg - lb	 N°	 N°
TRL PLUS 230	2523 - 1415 - 1177	2245 - 88	540	90 - 67	5	850 - 1874	72	24
TRL PLUS 250	2652 - 1415 - 1177	2400 - 94	540	95 - 71	5	940 - 2072	78	26
TRL PLUS 280	2995 - 1415 - 1177	2740 - 108	540	100 - 75	5	1024 - 2257	90	30
TRL PLUS 300	3185 - 1415 - 1177	2930 - 115	540	110 - 81	5	1085 - 2390	102	34



TRL PLUS